



## Serenity Collection

### Features and Benefits:

- Durable
- Warm to the touch
- Soft under foot
- Easy to maintain
- Anti-static
- Anti-bacterial
- Unilin locking system
- Precision, easy, self-locking system
- Thermal insulation
- Acoustic insulation
- Hypo-allergenic
- Use with in-floor radiant heating systems
- Resistant to fading
- Hot Coating provides durability for commercial application

### Technical Data:

Dimensions: 915mm x 305mm	(EN 427)
Total thickness: 11 mm	(EN 428)
Dimensional stability: <0,10 %	(EN 434)
Abrasion resistance: WR4	(EN 13534)
Abrasion resistance: AC 5	(EN 13329)
Total weight: ca. 8.000 g/m <sup>2</sup>	(EN 430)
Residual indentation: max. 0,14 mm	(EN 433)
Reaction to fire: Cfl-S1	(DIN 4102)
Impact sound reduction: 18 dB	(EN 140)
Thermal resistance: 0,11 m <sup>2</sup> K/W (RTD 133)	(EN 12524)
Chemical resistance: Good	
Weight resistance: Gr. Kugel: 2000 mm / Kl. Kuel: 35N	(EN 438-89)
Swelling value HDF: < 8%	(EN 317)
Coefficient of friction: R9	(DIN 51130)
Scratch resistance: 2N	(EN 438-2)