



## WE Cork Underlayment: *WECU-SILENTLY*

2mm Rubber and Cork underlayment for LVT and Linoleum floor covering featuring:

- **Sound Control**

*WECU-Silently* offers superior in room as well as floor to ceiling sound control with minimum thickness.

- **Thermal insulation**

*WECU-Silently* provides thermal insulation from cold subfloors

- **Comfort Under Foot**

*WECU-Silently* provides resilience and comfort to LVT and Linoleum flooring.

- **Environmentally Friendly**

*WECU-Silently* has 100% recycled content

### Technical Specifications

Description: Cork and rubber composition with polyurethane binder

Size: 2mm x 40" x 50'

Density: 40-46 lbs/ft<sup>3</sup>

Performance:

ASTM E2179-09 Delta Impact Insulation Class (IIC) under 2mm LVT: ΔIIC 20

ASTM C 518 Thermal conductivity (kcal/m.h. °C): .0775

ASTM F 152 Tensile strength (kPa): ≥ 600

Castor Test: ≥ 25000 revolutions

Packaging: 166.66 s.f./roll

25 rolls/pallet

Weight: 55 lbs/roll

### Installation Instructions

*WECU-Silently* should be removed from packaging and acclimated for 24-48 hours in room temperature between 65 and 84 Fahrenheit and humidity not to exceed 75%.

Subfloor Prep: Floor must be level, clean and dry.

All concrete subfloors should be tested for moisture

Use only APA underlayments and only Portland Cement base patching and leveling compounds.

Follow flooring manufacturer's recommended adhesive instructions to install *WECU-Silently* using suggested trowel size. Use same adhesive to install flooring on *WECU-Silently*.



[www.wecork.com](http://www.wecork.com) 800/666-2675