

Floating Floor MSDS

Product: HDF Board
Company: WE Cork, Inc.

Composition Information of the Ingredients

	<u>Concentration:</u>
-Timber	70-80%
-UMF Resin (Urea Melamine Formaldehyde)	12-20%
-Paraffin Wax	1-3%
-Formaldehyde	<0.008%

Hazards Identification:

- No hazards are described during handling of boards
- During manipulation of boards (cutting, machining, sanding) dust wood or traces of formaldehyde could be liberated.
- Risk of weak irritation to the skin or respiratory system could be possible in some of these cases.

First Aid Measures:

- In case of fire or irritation, move exposed people to a well ventilated place.
- If it is necessary, summon a doctor

Accidental Release Measures:

- Not applicable

Handling and Storage:

- Safe handling advice: Do not store boards higher than 4 meters high.
- Requirements for storage rooms: Storage area has to be indoor, well ventilated and damp free.

Exposure Controls/Personal Protection:

Occupational Exposure Limits

See local requirements, if occupational exposure limits are available.

Dust Wood:	TLV-TWA:	05 mg/m ³
Formaldehyde:	TLV-STEL:	0.3 ppm, 0.37 mg/m ³

Respiratory Protection: Wear suitable respiratory protective equipment if exposure levels above the occupational exposure limit is likely.

Eye Protection: Wear eye/face protection

Hand Protection: Wear suitable gloves.

Physical and Chemical Properties:

Form:	Solid
Color:	Green
Odor:	Wood
Boiling point:	No data
Melting point:	No data
Auto-ignition temperature:	175 degrees C.
Explosion limits:	Lower: not applicable Higher: not applicable
Density:	800-950 kg/m ³
Solubility in water:	not applicable
Explosive properties:	not applicable
Oxidizing properties:	not applicable

Toxicological Information:

Delayed or chronic toxicological effects: Risk of weak irritation to skin or respiratory system could be possible.